

H30D Circular truss - Allowable Loading																					
Diameter		3 Suspension Points				4 Suspension Points				6 Suspension Points				8 Suspension Points				10 Suspension Points			
		UDL		CPL		UDL		CPL		UDL		CPL		UDL		CPL		UDL		CPL	
m	ft	kg/m	lbs/ft	kg	lbs	kg/m	lbs/ft	kg	lbs	kg/m	lbs/ft	kg	lbs	kg/m	lbs/ft	kg	lbs	kg/m	lbs/ft	kg	lbs
4,00	131	114	7 681	316	698	203	13 693	455	1004	408	27 459	684	1509	619	41 660	837	1848	827	55 669	935	2065
6,00	197	57	3 852	230	508	109	7 340	346	765	238	16 001	563	1243	378	25 425	729	1609	519	34 901	845	1866
8,00	262	34	2 269	181	399	68	4 564	279	617	158	10 632	478	1056	261	17 564	645	1424	367	24 691	771	1701
10,00	328	22	1 460	148	328	46	3 091	234	516	113	7 616	416	918	193	13 011	551	1216	278	18 682	674	1488
12,00	394	15	1 004	126	278	33	2 210	201	443	85	5 730	362	798	150	10 083	467	1031	219	14 761	588	1298
14,00	459	11	722	109	240	24	1 641	176	388	63	4 210	306	675	114	7 658	397	877	179	12 021	502	1107